

Floats (for Pegler float operated valves)

Range	Code	Connection to lever arm*	Total (kg)
3" x 5/16" W	596022	5/16" W	0.03
4 1/2" x 5/16" W	596032	5/16" W	0.092
5" x 5/16" W	596033	5/16" W	0.114
6" x 3/8" W	596025	3/8" W	0.168
6" x 7/16" W	596026	7/16" W	0.170
8" x 3/8" W	596028	3/8" W	0.408
10" x 1/2" W	596029	1/2" W	0.803
10" x 9/16" W	596036	9/16" W	0.690
12" x 1/2" W	596038	1/2" W	0.788
12" x 5/8" W	596031	5/8" W	0.914

specification

- plastic or copper ball
- stud or claw attachment



Copper float sizes		
Range	Code	Total (kg)
4 1/2"	596001	0.121
5 1/2"	596003	0.183
6"	596004	0.219
8"	596006	0.442
10"	596008	0.686
12"	596009	1.005
14"	596010	2.420
15"	596011	2.390
16"	596012	2.766

Brass studs for copper floats. Required for copper float 4 1/2" to 12"		
Connection to lever arm*	Code	Total (kg)
5/16" W	596039	0.020
3/8" W	596040	0.020
7/16" W	596041	0.055
1/2" W	596042	0.104
9/16" W	596043	0.098
5/8" W	596044	0.187



Claws for copper floats. Required for copper float 12" to 16"		
Connection to lever arm*	Code	Total (kg)
9/16" W	596047	0.332
3/4" W	596048	0.313
7/8" W	596049	0.532



* W - Whitworth thread

Note: Studs generally required for float valves up to 2", Claws for 2 1/2" - 6" valves.

Note: Ball floats are only supplied in export shipments.