

Pegler type A draincock LS M R1/2" (DN15)



group: 833GMLS item: 542037 category: valves




The Prestex 833GM LS is a gunmetal draincock with lock shield and male tapered thread. By using Prestex in your piping system you can install in easy to use heat free system. Prestex provides a piping suitable for domestic and light commercial applications.

- No need for use of naked flames
- Can be used on wet pipework
- Joints can be dismantled without adversely affecting performance
- Provided with all relevant approvals

this article is part of a product group (833GMLS) that contains a total of 1 items

[view all 1 items](#)


applications

-  potable water
-  heating
-  cooling

segments



approvals



specifications - characteristics

color	bronze
materials	bronze (EN CC499K)
finishing	none
shape	straight (0°)
connection type	R - male thread gas conical (BSPT), hose connector
pressure rating (PN)	PN 20
sealing	EPDM

specifications - general

product group	valves (fill and drain valves)
ETIM class	EC010985 Drain valve (radiator and tap water)
HS code	84818019
brand	Pegler
series	Draincock
product type	833GMLS
UNSPS	40141654

specifications - product info

item	Pegler type A draincock LS M R1/2" (DN15)
item number with gtin	542037 (05013866007903)
product number with gtin	542037 (05013866017322)
manufacturer	Aalberts integrated piping systems Ltd (Pegler)
item group	833GMLS - Draincock
size	R1/2"

specifications - technical

max operating pressure liquid	20 bar
min. medium temperature	30 °C
max medium temperature	120 °C
peak medium temperature	110 °C

d1	DN1	l1	z1	slw1	l2	slw2	V	a
d1	DN1	l1	z1	slw1	l2	slw2	V	a
15.0	1/2" (DN15)	19	5	25	39	19	13	55

