

18V ONE+™ Rotary Tool Station,  
with 35 accessories (Bare Tool)  
RRTS18-0A35

**RYOBI**

**ONE+** **3**  
YEAR



- The powerful motor delivers up to 35,000 rpm. The variable speed control ranging from 2,600 - 35,000 rpm, allows for fine control when used on a variety of materials
- The quick-change chuck allows for quick and easy change of accessories (3.2 mm)
- The base station features on-board accessory storage for ease of use
- A slim line pen design helps allow for maneuverability and control



|                                       |                |
|---------------------------------------|----------------|
| Power                                 | 18V            |
| Collet capacity (mm)                  | 3.2            |
| Cable length [cm]                     | 92             |
| No load speed (rpm)                   | 2,600 - 35,000 |
| Weight with battery pack (EPTA) (kg)  | 1.58           |
| Article Number                        | 5133005637     |
| Battery pack capacity (Ah)            | -              |
| Charger included                      | No             |
| EAN Code                              | 4892210205018  |
| No. of batteries supplied             | 0              |
| Sound power level (Lwa) (dB(A))       | 89.7           |
| Sound power level uncertainty (dB(A)) | 3              |
| Sound pressure level (Lpa) (dB(A))    | 78.7           |
| Sound pressure level (dB(A))          | 3              |

\*Registration required for extension from 2-3 years. Please visit our site for full T&C's

ryobitools.eu

|                                     |   |
|-------------------------------------|---|
| Standard equipment                  | 35 accessories - (1.6mm engraving cutter, 3.2mm drill bit, 3.2mm high speed cutter, 2x 13mm and 2x 25mm felt polishing wheels, polishing mandrel, polishing compound, 19mm carbon steel brush, 5x 6.4mm sanding bands (2x 60 grit, 3x 120 grit), 7x 13mm sanding bands (2x 60 grit, 2x 120 grit, 3x 240 grit), 6.4mm sanding mandrel, 13mm sanding mandrel, 3x aluminium oxide grinding stones (1x 9.5mm cylindrical, 1x 9.5mm conical, 1x 6.4mm conical), 2.4mm diamond wheel point, 6x 38mm EZ cut off wheels, 3.2mm EZ mandrel), Accessory storage case and wrench |
| Supplied in                         | Over 75% recycled cardboard carton  |
| Vibration level (m/s <sup>2</sup> ) | 28.7  |